

SPU.

SENSORS (6-S & 7-S)



SPU.6-S & SPU.7-S SENSORS

Fully intelligent and addressable sensors



KEY FEATURES




Suitable for suspended or plasterboard ceilings | Flexible configuration options | 360 degree PIR presence detection | Simple LV bus connection to lighting control module | Wide range linear photocell | LED status indicator | Programmable infra-red receiver

TECHNICAL SPECIFICATION

SUPPLY | Two-wire E-Bus or DALI

WEIGHT | 60g

INGRESS PROTECTION | IP20



	SPU.6-S	SPU.7-S
Presence detection - 360 degree	✓	✓
High performance photocell 2-2000 lux	✓	
Infra-red receiver	✓	✓
Flexible configuration via SPECS manager graphical software	✓	✓
Connects to E-Bus or DALI pair	✓	✓
Each control element (PIR, PC, IR) can be seperately configured	✓	✓
Device status feedback	✓	✓
Suitable for suspended or solid ceilings	✓	✓
Mounted in pre-cut 66mm diameter hole	✓	✓

CONTACT US

T | 01992 450126

E | SALES@SIMMTRONIC.COM

E | AFTERSALES@SIMMTRONIC.COM

W | WWW.SIMMTRONIC.COM

HQ | LONDON & SOUTH

WATERSIDE

CHARLTON MEAD LANE

HODDESDON, HERTFORDSHIRE

EN11 0QR

MIDLANDS & NORTH

BLOC

17 MARBLE STREET

MANCHESTER

M2 3AW

SIMMTRONIC